



Features

- 24VDC Class 2 for wet locations
- Single micro binned LEDs +/- 30 CCT
- Fixtures made to order up to 144"
- Dims with minimal color shift
- Fixtures can be linked up to 35' depending on output
- Class 2 listed for wet locations
- 3 Year warranty
- Dot free even illumination achievable in SOHD & VHO with frosted lens (VHO model only)
- Vibrant colors with R9 values up to 98

IP68



IC RATED

RoHS Compliant



Finish options



Silver anodized



Black powder coated




Bronze powder coated



White powder coated

Profile dimensions



Technical information

OUTPUT OPTIONS

Output	Lumens at 3000K (with clear lens)	Average power consumption at 4'	Lumens / Watt (with clear lens)	Maximum system length in series
SO (LL36)	192	3.2 W/ft	60 lm/W	35'
SOHD (LL72-LO)	226	4.0 W/ft	57 lm/W	24'
HO (LL54)	301	5.2 W/ft	58 lm/W	26'
VHO (LL72)	411	6.5 W/ft	63 lm/W	18'

CCT INFO/LUMEN MULTIPLIER

Color temperature	Multiplier (reference - 3000K)	CRI	R _f	R _g
2700K	0.81	97	95	101
3000K	1.00	91	89	98
3500K	1.05	94	90	102
4000K	1.28	94	86	96

TM-30-15


Ordering code

MODEL	LENGTH	CCT	OUTPUT	LENS	MOUNTING	FINISH	POWER FEED POSITION / TYPE	ACCESSORIES	
KSW	12	27K	SO	C	FC	SA	E	1	BLS
KSW Kendo S Wet	12" - 144" 4" increments	27K - 2700 K 30K - 3000 K 35K - 3500 K 40K - 4000 K	SO - Standard SOHD - Standard High Density HO - High VHO - Very High	C - Clear F - Frosted	FC - Fixed clip AH - Adjustable hinge mounting FC45 - Fixed clip 4.5 degree	SA - Silver BK - Black BZ - Bronze WH - White [BK, BZ, WH finishes will have an upcharge and require longer lead times]	E - End B - Bottom	1 - 72" wire leads 1X2 - 72" wire leads at both ends 2 - 72" wire leads at one end and quick connect at other 3 - Single quick connect 4 - Dual quick connect	- N/A, leave blank BLS - Blade louver, Silver BLBK - Blade louver, Black BLWH - Blade louver, White GSS - Glare shield, Silver GSBK - Glare shield, Black GSWH - Glare shield, White


Power consumption per fixture length

Based on operation with PSD series of power supplies.

Nominal Length	Actual Length	SO		Actual Length	SOHD		Actual Length	HO		Actual Length	VHO	
		W/ft	Total wattage		W/ft	Total wattage		W/ft	Total wattage		W/ft	Total wattage
12"	12-12/16"	3.25	3.25	12-11/16"	4.20	4.20	12-11/16"	5.35	5.30	12-11/16"	6.75	6.75
16"	16-10/16"	3.25	4.00	16-9/16"	4.23	5.66	16-10/16"	5.33	7.06	16-9/16"	6.75	9.00
20"	20-10/16"	3.25	5.25	20-9/16"	4.27	7.12	20-10/16"	5.31	8.82	20-9/16"	6.75	11.25
24"	24-8/16"	3.25	6.50	24-8/16"	4.30	8.60	24-9/16"	5.30	10.60	24-8/16"	6.75	13.50
28"	28-7/16"	3.25	7.75	28-7/16"	4.20	9.77	28-7/16"	5.28	12.33	28-7/16"	6.75	16.75
32"	32-7/16"	3.25	8.50	32-6/16"	4.10	10.94	32-7/16"	5.26	14.06	32-6/16"	6.75	19.00
36"	36-5/16"	3.25	9.75	36-5/16"	4.00	12.10	36-6/16"	5.25	15.80	36-5/16"	6.65	19.95
40"	40-4/16"	3.25	10.25	41-4/16"	4.00	13.43	40-5/16"	5.23	17.40	41-4/16"	6.65	22.20
44"	44-4/16"	3.20	11.75	45-3/16"	4.00	14.76	44-4/16"	5.21	19.00	45-3/16"	6.65	24.40
48"	48-3/16"	3.20	12.80	49-2/16"	4.00	16.10	48-3/16"	5.20	20.60	49-2/16"	6.55	26.20
52"	52-2/16"	3.20	13.30	53-1/16"	3.97	17.27	53-7/16"	5.18	22.40	53-1/16"	6.55	28.50
56"	56-1/16"	3.20	14.80	57 "	3.95	18.44	57-6/16"	5.16	24.20	57 "	6.55	30.50
60"	60 "	3.20	16.00	60-15/16"	3.92	19.60	61-5/16"	5.15	26.00	60-15/16"	6.45	32.25
64"	63-15/16"	3.20	17.00	64-14/16"	3.89	20.73	65-4/16"	5.13	27.60	64-14/16"	6.45	34.40
68"	69-13/16"	3.15	18.00	68-13/16"	3.86	21.86	69-3/16"	5.11	29.20	68-13/16"	6.45	36.55
72"	73-12/16"	3.15	18.90	72-12/16"	3.83	23.00	73-2/16"	5.10	30.80	72-12/16"	6.40	38.40
76"	77-11/16"	3.15	19.00	76-11/16"	3.80	24.06	77-1/16"	5.08	32.40	76-11/16"	6.40	40.50
80"	81-11/16"	3.15	21.50	80-10/16"	3.83	25.12	81-1/16"	5.06	34.00	80-10/16"	6.40	43.00
84"	85-9/16"	3.15	22.05	84-9/16"	3.74	26.20	85 "	5.05	35.70	84-9/16"	6.25	43.75
88"	89-8/16"	3.15	23.00	88-8/16"	3.73	27.33	88-14/16"	5.03	37.10	88-8/16"	6.25	46.00
92"	93-7/16"	3.10	24.00	92-7/16"	3.71	28.46	92-13/16"	5.01	38.50	92-7/16"	6.25	48.00
96"	97-6/16"	3.10	24.80	97-6/16"	3.70	29.60	96-13/16"	5.00	40.00	97-6/16"	6.15	49.20
100"	101-6/16"	3.10	26.30	101-5/16"	3.67	30.56	100-12/16"	4.98	41.60	101-5/16"	6.15	51.25
104"	105-4/16"	3.05	27.10	105-3/16"	3.64	31.53	104-11/16"	4.96	43.20	105-3/16"	6.15	53.00
108"	109-4/16"	3.05	28.00	109-3/16"	3.61	32.50	108-10/16"	4.95	44.80	109-3/16"	6.00	54.00
112"	113-3/16"	3.05	28.50	113-2/16"	3.59	33.46	112-9/16"	4.93	46.20	113-2/16"	6.00	56.00
116"	117-1/16"	3.05	30.00	117-1/16"	3.56	34.43	116-8/16"	4.91	47.60	117-1/16"	6.00	58.00
120"	121-1/16"	3.00	30.50	121 "	3.54	35.40	120-8/16"	4.90	48.90	121 "	5.90	59.00
124"	125 "	3.00	31.50	124-15/16"	3.52	36.36	124-7/16"	4.88	50.40	124-15/16"	5.90	60.60
128"	128-14/16"	3.00	32.50	128-14/16"	3.50	37.33	128-6/16"	4.86	51.90	128-14/16"	5.90	62.20
132"	132-14/16"	2.95	33.50	132-13/16"	3.48	38.30	132-5/16"	4.85	53.30	132-13/16"	5.80	63.80
136"	136-13/16"	2.95	34.30	136-12/16"	3.46	39.20	136-4/16"	4.83	54.70	136-12/16"	5.80	65.30
140"	140-12/16"	2.95	35.20	140-11/16"	3.44	40.10	140-3/16"	4.81	56.10	140-11/16"	5.80	66.80
144"	144-11/16"	2.90	36.00	144-10/16"	3.42	41.00	145-7/16"	4.80	57.40	144-10/16"	5.70	68.40




Connectors




Linking and Extension Cable


Male/female Joiner 12" - Part # IP67-12




Male/female Joiner 48" - Part # IP67-48




Powerfeed options with fixed bracket




72" wire leads (1)




72" wire leads at one end and quick connect at other (2)



Single quick connect (3)




Dual quick connect (4)




Accessory options


Glare Shield:
redirect the light to avoid glare from fixture
available only with complete fixture
reference page 1 ordering code




Blade Louver:
control light distribution
available only with complete fixture
reference page 1 ordering code




Splice Box:
Wet rated, low voltage
splice box, gray
Part # LVSP-WET



Connector:
Low voltage splice box
wet cable management
gray
Part # LVSP-WET-CM



Sample layout of powerfeed connections




Power supply

See fixture and power supply instructions & spec sheet for wiring information. Dimming possible in select models - view Luminii website for list of compatible dimmers.

Magnetic Low Voltage Dimming Power Supplies:

MODEL	POWER	OUTPUT	INPUT
PSD	48	24	
PSD - PSD Series dims down to 0%	48 - 48 W 96 - 96 W 288 - 288 W (3x 96W)	24 - 24 VDC	Blank - 120 V 240 - 240 V 277 - 277 V


MODELS	PSD 48	PSD 96	PSD 288
A Length	11.25"	11.25"	13.06"
B Width	3.42"	3.42"	8.42"
C Depth	3.42"	3.27"	4.47"



Electronic Low Voltage Dimming Power Supplies:

MODEL	CIRCUIT x POWER	OUTPUT	INPUT
CVE	48D	24	
CVE - CVE Series dims down to 0.1%	48D - 48W 48X2D - 2 x 48W 48X3D - 3 x 48W 48X4D - 4 x 48W 96D - 96W 96X2D - 2 x 96W 96X3D - 3 x 96W 96X4D - 4 x 96W	24 - 24 VDC	Blank - 120 V 277 - 240/277 V


MODELS	Single circuit	Dual circuit	Three circuit	Four circuit
A Length	13.9"	13.8"	13.8"	13.8"
B Width	2.3"	4.0"	5.9"	7.75"
C Depth	1.3"	1.9"	1.9"	1.9"



0-10V Dimming Power Supplies:


MODEL	POWER	OUTPUT	DIMMING
PS010V	3X96	24	LIN
PS010V - 0-10V Power Supply dims down to 0%	96 - 96 WATT 3X96 - 3 X 96 WATT	24 - 24 VDC	LIN - Linear LOG - Logarithmic

MODELS	96 W	3X96
A Length	14.40"	15.75"
B Width	5.20"	6.60"
C Depth	2.60"	4.80"



MODEL	POWER	OUTPUT	DIMMING	LOCATION
PSV	40	24	U2DIM	D
PSV - PSV Series dims down to 5%	40 - 40 W 60 - 60 W 96 - 96 W	24 - 24 VDC	U2DIM - Dimming 0-10V	D - Dry Location IP65 - Wet Location

MODELS	PSV Dry	PSV Wet
A Length	9.2"	9.5"
B Width	3.4"	4.12"
C Depth	1.9"	2.3"



Power supply


See fixture and power supply instructions & spec sheet for wiring information. Dimming possible in select models - view Luminii website for list of compatible dimmers.

DMX Dimming Power Supplies:

MODEL	POWER	OUTPUT
PSDMX	96	24
PSDMX - DMX Power Supply	96 - 96 WATT 3X96 - 3 X 96 WATT	24 - 24 VDC

- Features eldoLED's LINEARdrive configurable dimmable drivers

MODELS	3X96 W
A Length	15.75"
B Width	6.60"
C Depth	4.80"




DALI Dimming Power Supplies:

MODEL	POWER	OUTPUT
PSDALI	96	24
PSDALI - DALI Power Supply dims down to 0%	96 - 96 WATT 3X96 - 3 X 96 WATT	24 - 24 VDC

- Features eldoLED's LINEARdrive configurable dimmable drivers

MODELS	96 W
A Length	14.40"
B Width	5.20"
C Depth	2.60"




Luminii is a Lutron OEM Advantage Partner

MODEL		
LTEA4U1UKL-CV240		
Lutron -Hi-lume™ 1% 2-wire LED driver (120V forward phase only)		


MODELS	LTEA	L3DA
A Length	4.89"	4.89"
B Width	2.66"	2.66"
C Depth	4.00"	4.00"

MODEL		
L3DA4U1UKL-CV240		
Hi-lume™ 1% EcoSystem Voltage LED Driver		



MODEL		
L3D0-96W24V-U		
Hi-lume™ 0.1% EcoSystem Voltage LED Driver with Soft-On, Fade-to-Black™		

MODELS	L3D0
A Length	10.50"
B Width	5.50"
C Depth	2.00"




Power supply

See fixture and power supply instructions & spec sheet for wiring information. Dimming possible in select models - view Luminii website for list of compatible dimmers.

Enlighted Enabled Dimming Power Supplies:

MODEL	POWER	OUTPUT	DIMMING	Location
PSV	96	24	ENL	D
PSV- LED Power Supply	96 - 96 WATT	24 - 24 VDC	ENL - Enlighted Dimming	D - Damp


MODELS	96 W
A Length	14.40"
B Width	5.20"
C Depth	2.60"



Non-Dimming Power Supplies:

MODEL	POWER	OUTPUT	DIMMING	LOCATION
PSV	40	24	U2ND	D
PSV - PSV Series	40 - 40 W 60 - 60 W 96 - 96 W	24 - 24 VDC	U2ND - Non Dimming	D - Dry Location IP65 - Wet Location

MODELS	PSV Dry	PSV Wet
A Length	9.2"	9.5"
B Width	3.4"	4.12"
C Depth	1.9"	2.3"



In ground, Electronic Low Voltage Dimming Power Supplies:

MODEL	CIRCUIT x POWER	OUTPUT	INPUT
IG-CVE	96X2	24	
IG-CVE - In ground CVE Series dims down to 0.1%	96X2 - 2 x 96W	24 - 24 VDC	Blank - 120 V 277 - 240/277 V

MODELS	Dual circuit
A Length	8.0"
B Width	8.0"
C Depth	8.0"

